

**Special features**

- Including 0.5 m connecting cable

Housing Material	Stainless steel, Die-cast aluminium	Working Temperature	-20 to 40 °C
Housing Color	Silver	Storage Temperature	-10 to 60 °C
Material of Lens	Glass	IP Protection Class	IP 67
Protection Class	Protection class I/protective grounding	Load Force max.	5 kN
Rated Input	12.2 W	Life Time L70 / B50	25000 h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Switching Cycles	100000
Power Supply Unit incl.	Yes	Power Consumption	13 kWh/1000h
Connection Cable Primary	Yes	Energy Efficiency Class	G
Primary Connection	Connection box		
Primary Cable Length	0.5 m		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	860 lm		
Luminous Efficiency	70.5 lm/W		
Rated Angle of Reflection	20 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		
Height	42 mm		
Diameter	173 mm		
Installation Depth	42 mm		
Cut Out Diameter	150 mm		
Product weight	1612 g		