

Datenblatt Art. 683.882

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

Spiralleitung

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Produkteigenschaften		Product attributes	
Arbeitslänge (AL)	7.500mm	Working length (WL)	7.500mm
Wendellänge (WL)	1.500mm	Coil length (CL)	1.500mm
Außendurchmesser (AD)	13,7mm	Outer diameter (OT)	13,7mm
Wendelinnendurchmesser (WID)	18mm	Coil Internal diameter (CID)	18mm
Wendelaußendurchmesser (WAD)	46mm	Coil external diameter (CED)	46mm
Leitungstyp	H07BQ-F	Cable type	H07BQ-F
Anzahl Adern	5G	Number of wires	5G
Querschnitt (je Ader)	2,5 mm ²	Diameter (per wire)	2,5 mm ²
Mantelisoliation	PUR	Sheath insulation	PUR
Aderisoliation	Gummi	Wire insulation	Rubber
Farbe Mantelisoliation	orange	Colour Sheath insulation	orange
Farbe Aderisoliation	braun, schwarz, grau, blau, grün-gelb	Colour wire insulation	brown, black, grey, blue, green-yellow
Seite 1	200mm glatt geschnitten	Side 1	200mm cut flush
Seite 2	200mm glatt geschnitten	Side 2	200mm cut flush
Lieferumfang	1x Spiralleitung	Scope of delivery	1x Spiral cable
Unverpackt		Unpacked	

