



The ALKES series is not a traditional wall-mounted light but reminds you of a floodlight with its SMD-LED panel. The highlight: the upper housing part is tilted forwards 45° from the façade to direct the warm white light in a targeted manner onto the surface to be illuminated. In addition, the ALKES also looks great when switched off with its modern design and rounded edges.

Special features

- High luminous efficacy
- Homogeneous light distribution
- Die-cast aluminium housing

Housing Material	Die-cast aluminium
Housing Color	Grey
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	36 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	Infrared
Detection Distance	1-10 m
Angle of Detection	100 Degree

Life Time L70 / B50	26500 h
Switching Cycles	15000
Power Consumption	36 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1720 lm
Rated Angle of Reflection	110 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	297 mm
Width	165 mm
Height	240 mm

Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 65