



MaxPower Industrial Co.,Ltd

Tel:86-755-2899 8225 Fax:86-755-8456 4506 Mobile:+86-13714669620

E-mail:Lucy@maxpowersz.com

www.maxpowersz.com

MaxPower BATTERY MATERIAL SAFETY DATA SHEET **PRODUCT NAME: NICKEL CADMIUM SEALED CELL BATTERY (Ni-Cd Series)**

Ref.No.:MP-W5-878D

1. Information of Manufacturer

Manufacturer Name Maxpower Industrial Co.,Ltd	Telephone Number for Information +86-755-2899-8225
Add:Building B,Fenglin International Centre, Shenhui Road,Longgang District,Shenzhen,China	Fax Number for Information +86-755-8456-4506

2. HEALTH HAZARD INFORMATION

<p><u>Effects of Overexposure</u></p> <p><u>Eye Effects:</u> In the case of a fire or cell rupture the electrolyte solution inside battery is extremely corrosive to eye tissue and may result in permanent blindness. Contact with nickel oxide may cause minor irritation.</p> <p><u>Skin Effect:</u> Contact with electrolyte solution inside battery may cause serious burns to skin tissues. Contact with nickel compounds may cause result in chronic eczema or nickel itch.</p> <p><u>Ingestion:</u> Ingestion of electrolyte solution causes tissue damage to throat area and gastro/respiratory tract. Ingestion of nickel compounds causes nausea and intestinal disorders.</p> <p><u>Inhalation:</u> No exposure possible except in the case of fire of abuse. Effects of inhalation of cadmium and/or nickel compounds vary from mild irritation of nasal mucous membranes to damage of lung tissues proper. Inhalation of cadmium oxide may cause dry throat, cough, headache, vomiting, chest pain and chills. Chronic overexposure to cadmium compounds may result in pulmonary edema, breathing difficulty, prostration, and kidney damage.</p>

3. EMERGENCY FIRST AID

<p><u>Battery Electrolyte:</u></p> <p><u>Eye Contact:</u> Flush with plenty of water for at least 15 minutes if abuse causes safety vents to activate. Get immediate medical attention.</p> <p><u>Skin Contact:</u> Remove contaminated clothing and flush effected areas with plenty of water for at least 15 minutes. Wash with soap and water.</p> <p><u>Ingestion:</u> Do not induce vomiting. Dilute by giving water. If available give several glasses of mild. Get immediate medical attention. Do not give anything by mouth to an unconscious person.</p> <p><u>Inhalation:</u> Remove to fresh air. Give oxygen or artificial respiration if needed. Get immediate medical attention.</p>



MaxPower Industrial Co.,Ltd

Tel:86-755-2899 8225 Fax:86-755-8456 4506 Mobile:+86-13714669620

E-mail:Lucy@maxpowersz.com

www.maxpowersz.com

4. REACTIVITY DATA

Incompatibilities: Aluminum, zinc and other active metals, acid, chlorinated and aromatic hydrocarbons, nitro carbons, halocarbons.

Hazardous Decomposition products: Nickel oxide, cadmium, cadmium oxide and potassium hydroxide.

Hazardous Polymerization will not occur.

5. SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use NOISH/MSHA approved respirator if cell broken open during a fire to maintain exposure levels below the TWA for cadmium and nickel compounds.

Eye Protection: Use splash goggles or face shield if cell activates due to abuse.

Hand Protection: If exposure to electrolyte solution, or dried salts is likely, use any water-insoluble non-performance glove, i.e., synthetic rubber. Do not use leather or wool.

Other protective equipment: Rubber apron or equivalent if exposure to electrolyte solution is likely.

6. FIRE AND EXPLOSION HAZARDS

Extinguishing Media

	Melting Point	Boiling Point
Cadmium	808° F	1410° F
Cadmium Oxide	N/A	2840° F
Nickel	2645° F	4850° F
Nickel Hydroxide	N/A	445° F(Decomposes to NiO)
Nickel Oxide	3605° F	90° F (Decomposes to Ni and O ₂)

Special Fire Fighting Procedure: Use self-contained breathing apparatus to avoid breathing toxic fumes. Wear protective clothing and equipment to prevent potential body contact with electrolyte solution or mixture of water and solution.

Fire and Explosion Hazards: Electrolyte solution is corrosive to all human tissues. It will react violently with many organic chemicals, especially nitro carbons and chlorocarbons. Electrolyte solution reacts with zinc, aluminum and other active materials, releasing flammable hydrogen gas.

Cadmium fumes may be released when batteries are subjected to high temperature. In case of fire, do not take in smoke and fume.



MaxPower Industrial Co.,Ltd

Tel:86-755-2899 8225 Fax:86-755-8456 4506 Mobile:+86-13714669620

E-mail:Lucy@maxpowersz.com

www.maxpowersz.com

7. Ingredients

EXPOSURE LIMITS

QUANTITY

Cadmium(as Cadmium, Cadmium Hydroxide, and Cadmium Oxide)	5 mog/m ³ dust – OSHA	≈17%
Nickel(as Nickel, Nickel Hydroxide, and Nickel Oxide)	1mg/ m ³ -OSHA	≈19%
KOH	2mg/ m ³ ACGIH Ceiling Air	≈1%
Cobalt Hydroxide (as Cobalt Metal)	0.1mg/ m ³ dust – OSHA	≈1%

8. PHYSICAL PROPERTIES

Boiling Point:	Not applicable	Melting pointing:	Not applicable
Vapor Pressure:	Not applicable	Vapor Density:	Not applicable
Specific Gravity:	1.17-1.250(electrolyte)	Evaporation Rate:	Not determined
Solubility in water:	Electrolyte solution is completely soluble		
REMAINDER:	INSOLUBLE		

9. SPILL MANAGEMENT PROCEDURES

Electrolyte Spill: Flush with water and neutralize with dilute vitriol.

10. DISPOSAL INFORMATION

Battery is TCLP Toxic. Battery and electrolyte solution are corrosive. If not recycled, must be disposed of in accordance with all international, national, provincial regulations.



11. PRECAUTIONS AND COMMENTS

These cells and batteries manufactured from them may be highly charged and are capable of high-energy discharge. Care should be taken to handle cells properly to avoid shorting or misuse that will result in rapid uncontrolled electrical, chemical, or heat energy release.

Do not short circuit---may cause burns.

Do not break open cell.

Do not allow an exposed flame or spark to come near the cells.

12. Storage Information

These cells and batteries shall not be stored in high temperature, the maximum temperature is 45°C (less than one month), otherwise the cells and batteries maybe leakage. Besides, the cells and batteries shall be protected from short circuit and protected from movement that could result in short circuit.

13. Ecological Information

N/A

14. Disposal Method

Disposal of batteries comply with government regulations.



MaxPower Industrial Co.,Ltd

Tel:86-755-2899 8225 Fax:86-755-8456 4506 Mobile:+86-13714669620

E-mail:Lucy@maxpowersz.com www.maxpowersz.com

15. Transportation Information

All of cells being transported by air, by sea, or by truck shall be protected from short circuit and protected from movement that could result in short circuit.

16. Regulatory Information

Special requirements shall comply with local regulations.

17. Other Information

The data in this MSDS relates only to the specific material designed herein.

18. Measure for fire extinction

In case of fire, it is permitted to use any class of extinguishing medium on those batteries or the packing material. Cool exterior of batteries if exposed to fire to prevent rupture. Fire fighters should wear self-contained breathing apparatus.

Date issued: 2021/12/12

Last Date Revised: 2022/02/10

