



The 3-in-1 ceiling light - with the Helen, you get three lights in one. The LEDs can be switched from warm white to neutral white or cold white using a small switch on the printed circuit board. Thanks to IP54, the ceiling light is suitable for all areas of the home, such as the kitchen, bathroom, living areas and even outdoors. The same light in both the garage and kitchen? No problem with the Helen. Whilst you would probably prefer cold white in the garage, warm white is the top pick for living areas and usually neutral white in the kitchen and bathroom. All bases are covered with just one light.

Special features

- Light colour adjustable in 3 stages
- Splash water protected

Housing Material	Plastic	IP Protection Class	IP 54
Housing Color	Silver	Life Time L70 / B50	30000 h
Housing Surface	Brushed	Switching Cycles	15000
Material of Lens	Polycarbonate - PC	Power Consumption	17 kWh/1000h
Colour of Lens	White	Energy Efficiency Class	G
Surface Structure of Lens	Satined		
Protection Class	Protection class II/protective insulation		
Rated Input	16.3 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000/5500 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	1400 lm		
Rated Angle of Reflection	115 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	83 mm		
Diameter	276 mm		
Base height	20 mm		
Base diameter	251 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-20 to 50 °C		

