



#### Product Features

DIN-rail mounting adapter, with Universal modular jack UM-Cat.6A iso A, 1 DIN unit wide (1 unit 17 mm)
- Cat.6A iso conform, for use in 10-Gigabit-Networks (transmission bandwidth 500 MHz)
- for DIN-rail mounting
- insulation class II (without earth connector)
- insulations class I (with earth connector)
- earthing connection via customary blade terminal
- RJ45-angle outlet (ra. 45°)
- plug unlocking at the frontside
- unloosable cover
- with labeling field
performance universal modular jack:
- Cat.6A iso universal module, shielded
- for use in 10-Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- 1 x RJ45 - opening
- for standard keystone cutouts (14,7 x 19,3mm)
- zinc diecast design
- nickel-plated housing
- 360° strain relief and shielding
- suitable for Cat.6 and Cat.7 cable (Ø 6-10mm)
- solid wires: IDC-terminals for one wire 0,51 - 0,64 mm Ø, AWG 24-22, maximum number of connections > 10-times
- stranded wires: IDC-terminals for one wire Leiter 0,13-0,22 mm Ø AWG 26 (PE-Foamskin), AWG 24 (PE-solid), outer diameter 0,9-1,1 mm (PE)
- 1 wire each contact, max. number of connections > 10-times
- bend radius optimized cable entry (30°)
- defined grounding via flat plug possible
- mounting without any special tools
- built-in dust protection (removeable)
- colour code T568A and T568B according to EIA/TIA 568 A and B
- suitable for PoE++ / 4PPOE according to IEEE 802.3bt
- UPOE conform
- HDBaseT conform
- with mounting adapter suitable for the TAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)
- according to the following standards:
- ISO/IEC 11801, Cat.6A, shielded
- DIN EN 50173-1, Cat.6A, shielded
- ANSI TIA/EIA-568-C.2 Category 6A
- DIN IEC 60603-7-51, 500 MHz, shielded,
- life > 750 cycles

- RJ11/12-protected against mismatching
- GHMT certified

**Features**

## General

Surface	high-gloss
Design	jack
Labeling field	Yes
shielded	Yes
Classification	Cat.6A iso
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921663813

## Mounting types

DIN-Rail	Yes
----------	-----

## Dimensions/Weights without packaging

Length mm	18
Width mm	73
Height mm	70
Net weight piece kg	0,052

## Certifications

WEEE	Yes
GHMT	Yes
CE	Yes
RoHS conform	Yes

## Logistics Information

Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	1
Packaging unit Width mm	312
Packaging unit Height mm	178
Packaging unit Depth mm	87

## References

Accessories	21207000, 39200002, 39200003
Similar article	13900304, 17000030

