

**Special features**

- Including 0.5 m connecting cable with protected connection socket

Housing Material	Die-cast aluminium
Housing Color	Black
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	6 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box
Primary Cable Length	0.5 m
Dimmable	No
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	5 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	520 lm
Luminous Efficiency	86.7 lm/W
Rated Angle of Reflection	24 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	63 mm
Width	63 mm
Height	90 mm
Installation Depth	155 mm
Cut Out Length	69 mm
Cut Out Width	69 mm

Product weight	674 g
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
IK Protection Class	IK06
Load Force max.	5 kN
Life Time L70 / B50	35000 h
Switching Cycles	20000
Power Consumption	7 kWh/1000h
Energy Efficiency Class	G