



#### Product Features

25/10 Gigabit-modular jack, shielded, 2-way, flush mounting with 2 modules, break off mounting ring, suitable for the design wall plates of all well-known manufacturer

- for use in 25-Gigabit-Ethernet Networks (bandwidth 1250 MHz)
- for use in 10-Gigabit-Ethernet Networks (bandwidth 500 MHz)
- RJ45 - openings
- suitable for the TAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)
- performance universal modular jack:
  - 25GB universal modular jack, shielded, for standard Keystone openings
  - 1 x RJ45 jack
  - for standard keystone cutouts (14,8 x 19,3mm)
  - zinc diecast design
  - nickel plated housing
  - suitable for cables with 6-10 mm diameter
  - solid wires: IDC-terminals for one wire 0,57-0,64 mm diameter
  - 1 wire for each contact, reconnectable 4-times (at the same or larger diameter)
  - shield contact regarding to standards
  - defined grounding via flat plug possible
  - easy to mount (2 pieces)
  - built-in dust protection (removable)
  - colour code T568A and T568B according to TIA/EIA-568 B.2
  - suitable für PoE+ (Power over Ethernet) according to IEEE 802.3at
  - UPOE conform
  - HDBaseT conform
  - with mounting adapter angled/straight
  - according to the following standards for 25Gbit:
    - ISO/IEC TR 11801-9905
    - ISO/IEC 11801, Class I bis 1250 MHz, shielded
  - according to the following standards for 10Gbit:
    - ISO/IEC 11801, Cat.6A, shielded
    - DIN EN 50173-1, Cat.6A, shielded
    - ANSI TIA/EIA-568-C2 Category 6A
    - DIN EN 60603-7-51, 500 MHz, shielded
  - life > 750 cycles
  - GHMT certified

Features	
General	
Support ring	Yes
Design	jack
Design capability	Yes
shielded	Yes
PoweroverEthernet	Yes
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921666715
Mounting types	
flush-mounted	Yes
surface-mounted	Yes
Dimensions/Weights without packaging	
Net weight piece kg	0,067
Certifications	
WEEE	Yes
GHMT	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	1,17
Packaging unit Width mm	178
Packaging unit Height mm	87
Packaging unit Depth mm	312
References	
Accessories	10010051, 13910053

