



MENKAR series pendant lamps impress with clever lighting functions and high-quality aluminium accents. The rear light, which can be switched on separately (approx. 15-20 % of indirect lighting component), allows continuous indirect lighting whilst the main light can be switched on at any time.

Special features

- Indirect and direct lighting
- Light colour adjustable in 2 stages
- Indirect lighting can be switched on separately
- Suspended mounting up to 1800 mm
- High luminous intensity

Housing Material	Aluminium
Housing Color	Black
Housing Surface	Matt
Material of Lens	Acryl
Surface Structure of Lens	Satined
Protection Class	Protection class I/protective grounding
Rated Input	65 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No
Light Source	LED, Light source changeable TC
Color Temperature	3000/4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	5600/6000 lm
Rated Luminous Flux 2	6000 lm
Light Distribution	Symmetric
Light Exit Surfaces	2
Light characteristics	Direct, Indirect
Light direction	Top, Below
Height	90 mm
Diameter	600 mm
Base height	40 mm
Base diameter	120 mm
Pendulum Length max.	1800 mm

Working Temperature	-10 to 45 °C
Storage Temperature	-10 to 45 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	20000
Power Consumption	65 kWh/1000h
Energy Efficiency Class Lightsources	This product contains light sources of energy efficiency classes E and F.