



#### Special features

- Light colour adjustable in 3 stages
- 230 V direct connection
- Including power supply

<b>Housing Material</b>	Aluminium	<b>IK Protection Class</b>	IK03
<b>Housing Color</b>	White	<b>Life Time L70 / B50</b>	50000 h
<b>Material of Lens</b>	Plastic	<b>Switching Cycles</b>	100000
<b>Protection Class Lamp</b>	Protection class III/safety extra-low voltage	<b>Power Consumption</b>	36 kWh/1000h
<b>Protection Class Power Plug</b>	Protection class II/protective insulation	<b>Energy Efficiency Class</b>	E
<b>Rated Input</b>	30.5 W		
<b>Rated Input Voltage</b>	220-240 V/AC		
<b>Power Supply Unit incl.</b>	Yes		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000/4000/6000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	3900/4320/4140 lm		
<b>Rated Luminous Flux 2</b>	4320 lm		
<b>Luminous Efficiency</b>	135.7 lm/W		
<b>Rated Angle of Reflection</b>	120 Degree		
<b>UGR</b>	22		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Length</b>	295 mm		
<b>Width</b>	1195 mm		
<b>Height</b>	32 mm		
<b>Working Temperature</b>	-20 to 45 °C		
<b>Storage Temperature</b>	-40 to 80 °C		
<b>IP Protection Class</b>	IP 40		