



Special features

- Ideal for homogeneous basic lighting
- Slim design
- Can be rotated and swivelled
- High luminous flux

Housing Material	Aluminium
Housing Color	White
Housing Surface	Matt
Material of Lens	Plastic
Surface Structure of Lens	Opal
Protection Class	Protection class I/protective grounding
Rated Input	21 W
Rated Input Voltage Frequency	110-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Adapter
Dimmable	No
Motion Detector	No
Light Source	LED, Light source not changeable
Lightcolor	Neutral white
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1500 lm
Luminous Efficiency	71.4 lm/W
Rated Angle of Reflection	115 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS
Swivel Angle	340 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below
Length	300 mm
Width	100 mm
Height	22 mm
Product weight	643 g

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	21 kWh/1000h
Energy Efficiency Class	G

