

recessed ceiling spot

Article no. 2170.02

Licht.
Für Generationen.

Entwurf

**Tender**

Deckeneinbauleuchte, chrom, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: GX5.3, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 50W, Amount of light sources / fittings: 1.0 Qty, Adjustability: Not adjustable, With control gear: No, control: Other.

| Article data | |
|--------------------|-----------------------|
| Article no. | 2170.02 |
| GTIN | 4250047755678 |
| Kurzbeschreibung | recessed ceiling spot |
| Material | Aluminium |
| Colour | Chrome |
| Type of surface | Glossy |
| Shape | Round |
| Outer diameter | 80 mm |
| Built-in diameter | 68 mm |
| Installation depth | 55 mm |
| weight | 0.000 kg |

recessed ceiling spot

Article no. 2170.02

Licht.
Für Generationen.

| Operating technology of the luminaires | |
|--|-----------------------------|
| System output | 50 W |
| Voltage type | AC/DC |
| AC nominal voltage max | 12 V |
| Frequenz max. | 50 Hz |
| Lamp | LV halogen lamp |
| Lamp holder | GX5.3 |
| Protection class | III |
| Degree of protection | IP20 |
| Control | Dimming depending on driver |

| Mounting technology | |
|-----------------------|---|
| Mounting method | Recessed mounting |
| Place of installation | Ceiling-mounted |
| Adjustability | Not adjustable |
| Further references | No cover with thermal insulation material |
| Circlip | Without circlip |

| Packing data | |
|---------------------|----------|
| Gross weight | 0.096 kg |
| Length of packaging | 85 mm |
| Packaging width | 43 mm |
| Packaging height | 84 mm |

| Compatible LED-modules | | | | | | |
|------------------------|-------|------------|--------------------|---------------|--------|------------------|
| Article no. | Power | Beam angle | Colour temperature | Luminous flux | Input | Height LED-Modul |
| 12925003 | 3 W | 38° | 2700 K | 290 lm | 350 mA | 40 mm |