



With its slim, unfussy housing design, the TUCANAE is a modern outdoor light that can be integrated almost anywhere. The 100-cm-high bollard light emits its warm white light diagonally downwards onto paths and other surfaces and, in the MOTION variant, has an integrated twilight switch with adjustable brightness threshold and operating time.

Special features

- Modern minimalist design
- Powerful and energy-saving
- Uniform illumination
- Adjustable brightness threshold and operating time [733068]
- Base L x W x H: 120 x 180 x 10 mm

Housing Material	Die-cast aluminium
Housing Color	Grey
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Rated Input	18 W
Rated Input Voltage Frequency	110-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	Infrared
Detection Distance	6-10 m
Angle of Detection	120 Degree

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1650 lm
Rated Angle of Reflection	110 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	206 mm
Width	180 mm
Height	1000 mm
Base length	120 mm
Base width	180 mm
Base height	10 mm

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 54

Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	18 kWh/1000h
Energy Efficiency Class	F