



Housing Material	Die-cast aluminium
Housing Color	White
Material of Lens	Plastic
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	10 W
Rated Input Voltage	14-15 V/DC
Rated Current	700 mA
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.5 m
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	700 lm
Luminous Efficiency	70 lm/W
Rated Angle of Reflection	30 Degree
Rated Angle of Reflection 2	90 Degree
Light Distribution	Asymmetric
Distribution Characteristic 120°	NDLS

Length	137 mm
Width	60 mm
Height	44 mm
Installation Depth	60 mm
Cut Out Length	130 mm
Cut Out Width	37 mm

Product weight	337 g
Working Temperature	-20 to 40 °C
Storage Temperature	-20 to 50 °C
IP Protection Class	IP 20
Life Time L70 / B50	20000 h
Switching Cycles	100000
Power Consumption	11 kWh/1000h
Energy Efficiency Class	G