


**Product features and key data**

<b>Luminaire type</b>	Exclusive free-standing LED luminaire with direct and indirect light output.		
<b>Mounting method</b>	Positioning		
<b>Luminaire optic</b>	With its wide, slightly asymmetric light distribution, the direct component of the luminaire provides very uniform illumination of the desk surface. The indirect component with Lambertian light distribution provides optimum room illumination.		
<b>LED-System</b>	HCL channel 1	HCL channel 2	HCL MAX
<b>Connected load</b>	118 W	104 W	110 W
<b>Colour temperature</b>	2.700 K	6.000 K	4.000 K
<b>Rated luminous flux</b>	15.300 lm	15.300 lm	15.300 lm
<b>Luminous efficacy</b>	129 lm/W	147 lm/W	139 lm/W
<b>Interchangeability lightsource</b>	Yes - interchangeable		
<b>Service life</b>	L80 (25 °C) = 50.000 h		
<b>Colour rendering index</b>	80		
<b>Colour tolerance</b>	3 SDCM		
<b>Photobiological class</b>	Group 0 - no risk		
<b>Luminaire colour</b>	RAL9005 Jet black		
<b>Luminaire body</b>	Luminaire body made of extruded aluminium profile and die-cast aluminium. U-shaped luminaire base. Lamp head inclination adjustable in longitudinal and transverse direction via two grub screws.		
<b>Electrical version</b>	With electronic control gear unit, dimmable (integrated).		
<b>Connection method</b>	Mains plug		
<b>Dimming range</b>	1 - 100 %		
<b>Mains frequency</b>	50/60 Hz		
<b>Mains voltage</b>	220 - 240 V		
<b>Total harmonic distortion &lt; %</b>	14 %		
<b>Ingress Protection (IP) rating</b>	IP20		
<b>Protection rating on room side</b>	IP20		
<b>Protection class</b>	I		
<b>Impact resistance (IK)</b>	IK02		
<b>Hot wire resistance</b>	650 °C		
<b>Ambient temperature</b>	25 °C		
<b>Max. Luminaires B10</b>	7		
<b>Max. Luminaires B16</b>	12		
<b>Max. Luminaires C10</b>	12		
<b>Max. Luminaires C16</b>	20		
<b>Net length</b>	677 mm		
<b>Net width</b>	320 mm		
<b>Net height</b>	2.000 mm		
<b>Weight</b>	16,9 kg		


light distribution curve



**LuceoS Act S G2 SMC PAW-IL 150 ETDI 05 (ACTCW)**  
**TX369936** ■ C0 - C180  
■ C90 - C270  
 DIN 5040: E43  
 UTE: 0,10 D + 0,90 T  
 CEN Flux Code: 52 86 97 10 100 49 82 98 90



**LuceoS Act S G2 SMC PAW-IL 150 ETDI 05 (ACTSU)**  
**TX369911** ■ C0 - C180  
■ C90 - C270  
 DIN 5040: E43  
 UTE: 0,10 D + 0,90 T  
 CEN Flux Code: 52 86 97 10 100 49 82 98 90



**LuceoS Act S G2 SMC PAW-IL 150 ETDI 05 (ACTWW)**  
**TX369366** ■ C0 - C180  
■ C90 - C270  
 DIN 5040: E43  
 UTE: 0,10 D + 0,90 T  
 CEN Flux Code: 52 86 97 10 100 49 82 98 90

Offer text

Exclusive free-standing LED luminaire with direct and indirect light output. For standard-compliant illumination of single and double workstations. With integrated light management for the synchronous daytime- and seasonally dependent control of light colour (circadian control) of both light emission surfaces. In terms of design and photometric properties, the free-standing luminaire harmonises with suspended and surface-mounted luminaires as well as other free-standing luminaire versions in the project. The luminaire is delivered in 4 packages to protect the individual components. With its wide, slightly asymmetric light distribution, the direct component of the luminaire provides very uniform illumination of the desk surface. The indirect component with Lambertian light distribution provides optimum room illumination. Glare evaluation according to UGR rating (EN 12464-1) < 16. VDU workstation-compliant in accordance with 12464-1 Luminaire luminous flux 15300 lm, connected load 118,00 W, luminous efficiency of luminaire 129 lm/W. Light colour variable (warm white - daylight white), correlated colour temperature (CCT) variable (2700 K - 6000 K), general colour rendering index (CRI)  $R_a > 80$ . Colour locus tolerance (initial MacAdam)  $\leq 3$  SDCM, Mean rated service life  $L80(t_{q, 25^\circ C}) = 50,000$  h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Luminaire body made of extruded aluminium profile and die-cast aluminium. U-shaped luminaire base. Lamp head inclination adjustable in longitudinal and transverse direction via two grub screws. Surface powder-coated satin matt, colour black (RAL 9005). Further colours available on request. Luminaire height: 2000 mm, Length / width of base: 500 mm / 320 mm, Length / width of luminaire head: 677 mm x 290 mm, High luminaire head: 23 mm. Supporting column dimensions: 50 mm x 28 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP20, impact resistance level in accordance with IEC 62262: IK02, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Weight: 16,9 kg. Connection via flexible connection cable 3 x 1 mm<sup>2</sup> (safety plug and C14 cold-device socket), length approx. 3000 mm. Alternative connector types available: Connection plug type J SEV, Switzerland, Connection plug type BS, British Standard 1363. With connection cable. With electronic control gear unit, dimmable (integrated). The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). With Smart Connect equipment for combination with a LiveLink Lightgrid Controller. The luminaire features an integrated daylight- and HF presence sensor with motion direction detection. LiveLink Workplace versions of luminaires in a room can be connected via Bluetooth to form an interactive group of luminaires. The initial detection of movement by any luminaire within the group causes all group devices to switch on at basic lighting level (approx. 300 lx, indirect component). Subsequent detection in the close range of a luminaire triggers this into workplace mode by switching on of the direct component Within the luminaire group, the light colour and HCL curve of the indirect component are harmonised. Parameterisation of the Smart Connect functions is password-protected using a smartphone and an app. Operating the lighting functions is implemented manually via 3 operating elements and via Smartphone app. Communication between the connected luminaires and the smartphone is via Bluetooth Low Energy v 5.0. Single luminaires as well as luminaire groups can be controlled with up to 4 battery-free and wireless radio buttons, which are available as separately ordered accessories. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.