Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | | | | | |
|--|------------------|-----------------------------|--|--------------|--|
| Supplier's name | e or trade mark: | EVN | | | |
| Supplier's addr | ess: EVN, Zum Li | chtblick 1-12, 90610 | Winkelhaid, DE | | |
| Model identifie | er: 12353502 | | | | |
| Type of light so | urce: | | | | |
| Lighting techno | logy used: | LED | Non-directional or directional: | DLS | |
| Light source cap-type (or other electric interface) | | GU4 | | | |
| Mains or non-m | | NMLS | Connected light source (CLS): | Nein | |
| Colour-tuneable | e light source: | Nein | Envelope: | - | |
| High luminance | light source: | Nein | | | |
| Anti-glare shield: | | Nein | Dimmable: | No | |
| Product parameters | | | | | |
| Parameter | | Value | Parameter | Value | |
| | | General product p | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 3 | Energy efficiency class | F | |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 216 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 | |
| On-mode power (P _{on}), expressed in W | | 2,7 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 | |
| Outer | Height | 36 | Spectral power | See image | |
| dimensions without | Width | 35 | distribution in the | in last page | |
| without | Depth | 35 | | | |

| | range 250 nm to 800 nm, at full-load | | | | |
|--|---|---|--|--|--|
| - | If yes, equivalent power (W) | - | | | |
| | Chromaticity | 0,434 | | | |
| | coordinates (x and y) | 0,397 | | | |
| Parameters for directional light sources: | | | | | |
| 486 | Beam angle in | 35 | | | |
| | degrees, or the | | | | |
| | range of beam | | | | |
| | angles that can be | | | | |
| | set | | | | |
| Parameters for LED and OLED light sources: | | | | | |
| 7 | Survival factor | - | | | |
| - | | | | | |
| | 486 ht sources: | nm, at full-load If yes, equivalent power (W) Chromaticity coordinates (x and y) ources: 486 Beam angle in degrees, or the range of beam angles that can be set ht sources: | | | |

(a)'-': not applicable; (b)'-': not applicable;

