



**Special features**

- Ultra-compact design
- Flicker-free
- Short-circuit-proof, overload protection, overheating protection

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Functions</b>	Short-circuit proof, Lamp control gear 110, Furniture installation, Protective extra-low voltage, Overloading protection, Overtemperature protection

<b>Operating Mode</b>	Constant current
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power</b>	1.4-12 W
<b>Output Voltage</b>	2-17 V/DC
<b>Output Current</b>	700 mA
<b>Power Factor</b>	0.90
<b>Connection Type</b>	Clamp

<b>Number of Circuit Breaker B10A max.</b>	11
<b>Number of Circuit Breaker B16A max.</b>	18
<b>Number of Circuit Breaker C10A max.</b>	24
<b>Number of Circuit Breaker C16A max.</b>	39
<b>Inrush Current max.</b>	10 A / 100 μs
<b>Capacitive Load</b>	427 μF
<b>Reference Point Tc</b>	85 °C
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>IP Protection Class</b>	IP 20

**Life Time** 30000 h

<b>Length</b>	128 mm
<b>Width</b>	50 mm
<b>Height</b>	14 mm
<b>Product weight</b>	75 g

