



<b>Housing Material</b>	Aluminium	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Color</b>	Silver	<b>Switching Cycles</b>	20000
<b>Housing Surface</b>	Brushed	<b>Power Consumption</b>	3 kWh/1000h
<b>Material of Lens</b>	Plastic	<b>Energy Efficiency Class</b>	G
<b>Surface Structure of Lens</b>	Satined		
<b>Protection Class</b>	Protection class III/safety extra-low voltage		
<b>Operating Mode</b>	Constant voltage		
<b>Rated Input</b>	2.5 W		
<b>Rated Input Voltage</b>	12 V/DC		
<b>Power Supply Unit incl.</b>	No		
<b>Connection Cable Primary</b>	Yes		
<b>Primary Connection</b>	Power plug		
<b>Connection Cable Secondary</b>	Yes		
<b>Secondary Connection</b>	Plug mini AMP		
<b>Secondary Cable Length</b>	1.5 m		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Color Temperature</b>	3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	160 lm		
<b>Rated Angle of Reflection</b>	120 Degree		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Length</b>	50 mm		
<b>Width</b>	50 mm		
<b>Height</b>	5 mm		
<b>Working Temperature</b>	-5 to 40 °C		
<b>Storage Temperature</b>	-10 to 40 °C		
<b>IP Protection Class</b>	IP 20		