



Abbildung ähnlich

Product Features

HDMI-terminal devices connection cable (male/male), 2 m, black

- fire behaviour: UL 94 VW-1
- ready to connect
- gold-plated contacts, multiple shielded
- ultra flexible sheath material, black
- up to 5000 bending cycles
- cable diameter 7,5 mm
- bend radius: 8 times outer diameter
- data rate up to 32,4 Gbit/s
- video: up to 8K / 120 fps, 30 Bit RGB Color, DSC, HDR, Forward Error Correction 4K / 60 Hz, picture format 21:9
- audio: up to 1536 kHz
- temperature range: 0° C bis 80° C

Features

General

| | |
|--------------------------|---------------|
| shielded | Yes |
| Statistical goods number | 85444290 |
| Country of manufacture | CN |
| GTIN (EAN) | 4043921667200 |

Dimensions/Weights without packaging

| | |
|---------------------|-------|
| Cable length mm | 2.000 |
| Cable diameter mm | 7,5 |
| Net weight piece kg | 0,158 |

Certifications

| | |
|--------------|-----|
| WEEE | Yes |
| RoHS conform | Yes |

Logistics Information

| | |
|--------------------------|---------|
| Packaging | polybag |
| Packaging unit Quantity | 1 |
| Packaging unit Weight kg | 0,163 |
| Packaging unit Width mm | 200 |
| Packaging unit Height mm | 25 |
| Packaging unit Depth mm | 160 |

References

| | |
|-------------|----------|
| Accessories | 17010500 |
|-------------|----------|