



Wand- und Deckenkrümmer 30° M32/M40 mit Flügel - Beflügelter Wand- und Deckenübergang mit 2-in-1 Sytsem für den Betonbau

- » Ein Krümmer für zwei Rohrgrößen
- » Durch Stecksystem am Frontteil aneinanderreihbar
- » Rohrgrip für sichere Zugentlastung
- » Absolut betondicht
- » Integrierte Schraubdome



Produkteigenschaften

Form	gekrümmt, 30°
Farbe	anthrazit / orange
Anzahl Teile	2
Abmessungen Unterteil (LxB)	65 x 64 mm
Länge Krümmer	79 mm
Durchmesser Krümmer	49 mm
Flügelspannweite	210 mm
Anzahl der Einführungen	1 x für M32 oder M40 Rohr
Anreihbar	Ja
Schraubdome	2
Aufnahme Deckenhaken	Nein
Luftdicht	Ja
Betondicht	Ja
Zugentlastet	Ja
Gegenlager	Bei Bedarf

Serie	-
Artikelnummer	P755
Kategorie	Betoninstallation
Montageart	Flügel, Nagel, Kleber
Einsatz	Ortbeton, Werkfertigung
EAN	4260182062944

Materialeigenschaften

Material	PP
----------	----



Product features

Shape	curved, 30°
Color	anthracite / orange
Number of parts	2
Dimensions lower part (LxW)	65 x 64 mm
Length transition	79 mm
Diameter transition	49 mm
Wing span	210 mm
Number of conduit entries	1 x M32 or M40 conduit
Bayable	Yes
Screw domes	2
Ceiling hook	No
Airtight	Yes
Concrete tight	Yes
Strain relief	Yes
Counter bearing necessary	If needed

Wall and ceiling transition 30° M32/M40 with wings - Winged wall and ceiling transition with 2-in-1 Sytsem for concrete construction

- » One elbow for two conduit sizes
- » Can be joined together by means of a plug-in system on the front part
- » Conduit grip for safe strain relief
- » Absolutely concrete-tight
- » Integrated screw domes

Series	-
Article No.	P755
Category	Concrete installation
Type of installation	Wings, nail, glue
Use	cast-in-place installation, prefabrication
EAN	4260182062944
Material properties	
Material	PP