

Recessed ceiling spot
Article no. 2375.25

Light.
For Generations.



Entwurf



Tender

recessed ceiling spot, alu. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: GU10, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Degree of protection: according to DIN EN 60529 IP44, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 11W.

| Article data | |
|-------------------|-----------------------|
| Article no. | 2375.25 |
| GTIN | 4250047755197 |
| Short description | Recessed ceiling spot |
| Colour | Alu |
| Type of surface | Matt |
| Length | 80 mm |
| Width | 80 mm |
| Hight | 105 mm |
| Weight | N.N. |

Recessed ceiling spot
Article no. 2375.25

Light.
For Generations.

| Operating technology of the luminaire | |
|---------------------------------------|-----------------------------|
| System output | 11 W |
| Voltage type | AC |
| AC nominal voltage max | 230 V |
| Frequenz max. | 50 Hz |
| Lamp | HV halogen lamp |
| Lamp holder | GU10 |
| Protection class | I |
| Degree of protection | IP44 |
| Control | Dimming depending on driver |

| Mounting technology | |
|-----------------------|-------------------|
| Mounting method | Recessed mounting |
| Place of installation | Ceiling-mounted |
| Material cover | Glass transparent |

| Packing data | |
|-------------------------|---|
| Gross weight | 0.52 kg |
| Length of packaging | 140 mm |
| Packaging width | 110 mm |
| Packaging height | 120 mm |
| Disposal at end of life | This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment. |

| Compatible LED-modules | | | | | | |
|------------------------|--|--|--|--|--|--|
| | | | | | | |