



SLIM series lights include single-luminaire and triple-luminaire pendant lamps and matching pendant lamps for the DEKO-LIGHT current track system. The light body in die-cast aluminium is always the same size (300 x 39 mm). Several SLIM models therefore can also be combined with each other in larger spaces. The pendant lamps for ceiling installation with max. 180 cm suspended mounting are available in a one or three-luminaire variant; three-luminaire variant both with long or round base depending on the arrangement of the lights.

Special features

- Die-cast aluminium
- Fabric cable
- Particularly glare-free thanks to low UGR value
- Suspended mounting up to 1800 mm

| | |
|--------------------------------------|-----------------------------------------|
| Housing Material | Aluminium |
| Housing Color | Black |
| Material of Lens | PMMA |
| Colour of Lens | Transparent |
| Surface Structure of Lens | Structured |
| Protection Class | Protection class I/protective grounding |
| Rated Input | 5 W |
| Rated Input Voltage Frequency | 200-240 V/AC 50 / 60 Hz |
| Power Supply Unit incl. | Yes |
| Connection Type | Clamp |
| Dimmable | No |
| Motion Detector | No |

| | |
|-----------------------------------------|----------------------------------|
| Light Source | LED, Light source not changeable |
| Color Temperature | 3000 K |
| Colour Consistency | 6 SDCM |
| Colour Rendering Index (Ra) | 90 |
| Rated Luminous Flux | 500 lm |
| Rated Angle of Reflection | 24 Degree |
| UGR | 19 |
| Light Distribution | Symmetric |
| Distribution Characteristic 120° | DLS |

| | |
|------------------------------|--------|
| Light Exit Surfaces | 1 |
| Light characteristics | Direct |
| Light direction | Below |

| | |
|-----------------------------|---------|
| Height | 300 mm |
| Diameter | 39 mm |
| Base height | 25 mm |
| Base diameter | 100 mm |
| Pendulum Length max. | 1800 mm |

| | |
|--------------------------------|--------------|
| Working Temperature | -20 to 45 °C |
| Storage Temperature | -20 to 65 °C |
| IP Protection Class | IP 20 |
| Life Time L70 / B50 | 50000 h |
| Switching Cycles | 100000 |
| Power Consumption | 5 kWh/1000h |
| Energy Efficiency Class | E |