



Special features

- Light colour adjustable in 3 stages
- Low glare value
- Low housing depth
- Optionally available as pendant lamp

| | | | |
|---|---|--------------------------------|--------------|
| Housing Material | Aluminium | Storage Temperature | -40 to 80 °C |
| Housing Color | White | IP Protection Class | IP 40 |
| Material of Lens | PMMA | IK Protection Class | IK03 |
| Protection Class | Protection class III/safety extra-low voltage | Life Time L70 / B50 | 40000 h |
| Operating Mode | Constant current | Switching Cycles | 100000 |
| Rated Input | 51.5 W | Power Consumption | 52 kWh/1000h |
| Rated Input Voltage | 33-38 V/DC | Energy Efficiency Class | F |
| Rated Current | 1500 mA | | |
| Power Supply Unit incl. | No | | |
| Dimmable | Yes | | |
| Control technology | Dimmable via optional power supply unit | | |
| Motion Detector | No | | |
| Light Source | LED, Light source not changeable | | |
| Color Temperature | 3000/4000/6000 K | | |
| Colour Consistency | 6 SDCM | | |
| Colour Rendering Index (Ra) | 90 | | |
| Rated Luminous Flux | 5300/6000/5700 lm | | |
| Rated Luminous Flux 2 | 6000 lm | | |
| Luminous Efficiency | 110.7 lm/W | | |
| Rated Angle of Reflection | 120 Degree | | |
| UGR | 22 | | |
| Distribution Characteristic 120° | NDLS | | |
| Light Exit Surfaces | 1 | | |
| Light characteristics | Direct | | |
| Light direction | Below | | |
| Length | 1195 mm | | |
| Width | 595 mm | | |
| Height | 9 mm | | |
| Working Temperature | -20 to 45 °C | | |