



Product Features

"Cat.6A iso-Patchpanel with 24 universal modules UM-Cat.6Aiso 10G, 19"/1 U, direct mounting, light grey (similar RAL 7035)"

- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)

- direct mounting

- 24 keystone openings

"- 19"/1 U, direct mounting"

- labelled ports (1-24)

- additional strain relief possibility for data cables with Cable ties

performance universal modular jack:

- Cat.6A iso universal module, shielded

- for use in 10-Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)

- 1 x RJ45 - opening

- for standard keystone openings (14,7 x 19,3mm)

- zinc diecast design

- nickel-plated housing

- 360° strain relief and shielding

- suitable for Cat.6 and Cat.7 cable (Ø 6-10mm)

- solid wires: IDC-terminals for one wire 0,51 - 0,64 mm Ø, AWG 24-22, maximum number of connections > 10-times

- flexibel wires: IDC-terminals for one wire Leiter 0,13-0,22 mmØ AWG 26 (PE-Foamskin), AWG 24 (PE-solid)

- 1 wire each contact, max. number of connections > 10-times

- bend radius optimized cable entry (30°)

- defined grounding via flat plug possible

- mounting without any special tools

- built-in dust protection (removeable)

- colour code T568A and T568B according to EIA/TIA 568 A and B

- suitable for PoE++ / 4PPOE according to IEEE 802.3bt

- UPOE conform

- HDBaseT conform

- with mounting adapter suitable for the TAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

- according to the following standards:

- ISO/IEC 11801, Cat.6A, shielded

- DIN EN 50173-1, Cat.6A, shielded

- ANSI TIA/EIA-568-C.2 Category 6A

- DIN IEC 60603-7-51, 500 MHz, shielded,

- life > 750 cycles

- RJ11/12-protected against mismatching

- GHMT certified

Features	
General	
Surface	steel sheet, powder-coated
Design	jack
shielded	Yes
Classification	Cat.6A iso
PoweroverEthernet	Yes
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921656433
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Dimensions/Weights without packaging	
Length mm	483
Width mm	108
Height mm	44
Net weight piece kg	1,55
Certifications	
GHMT	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	1,7
Packaging unit Width mm	510
Packaging unit Height mm	150
Packaging unit Depth mm	55
References	
Accessories	21207000, 23510002, 23510003, 23510004, 23510005, 23510006, 23510007, 39200002, 39200003
Similar article	236101100, 238101100, 239000000, 23910206, 23910208, 23910212

