



| | | | |
|--------------------------------------|---|---|--|
| Housing Material | Steel | Storage Temperature | -40 to 85 °C |
| Housing Color | Black | IP Protection Class | IP 20 |
| Material of Lens | PMMA | IK Protection Class | IK03 |
| Protection Class | Protection class I/protective grounding | Life Time L70 / B50 | 60000 h |
| Rated Input | 20 W | Life Time L80 / B50 | 60000 h |
| Rated Input Voltage Frequency | 220-240 V/AC 50 / 60 Hz | Switching Cycles | 100000 |
| Power Supply Unit incl. | Yes | Power Consumption | 20 kWh/1000h |
| Connection Type | Adapter | Energy Efficiency Class Lightsources | This product contains a light source of energy efficiency class B. |
| Dimmable | No | | |
| Motion Detector | No | | |
| Light Source | LED, Light source changeable TC | | |
| Lightcolor | Warm white (WW) | | |
| Color Temperature | 3000 K | | |
| Colour Consistency | 3 SDCM | | |
| Colour Rendering Index (Ra) | 90 | | |
| Rated Luminous Flux | 3200 lm | | |
| Luminous Efficiency | 160 lm/W | | |
| Rated Angle of Reflection | 60 Degree | | |
| UGR | 19 | | |
| Light Distribution | Symmetric | | |
| Swivel Angle | 30 Degree | | |
| Light Exit Surfaces | 1 | | |
| Light characteristics | Direct | | |
| Light direction | Below | | |
| Length | 600 mm | | |
| Width | 60 mm | | |
| Height | 54 mm | | |
| Product weight | 700 g | | |
| Working Temperature | -25 to 40 °C | | |