



Classic design interpreted in a modern way - the ADHARA made from aluminium captivates with its classic lines, ultra-modern materials and high degree of flexibility. The ADHARA can be optimally adjusted to any situation via its two or three joints. Its powerful LED module delivers 950 lumens and can also be dimmed thanks to a touch sensor. Whether for the boss's office or for a child's desk, the ADHARA looks great anywhere.

#### Special features

- Can be rotated and swivelled via joints
- Dimmable in 3 stages using touch sensor
- High luminous flux
- Ready to use

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Silver
<b>Material of Lens</b>	Plastic
<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	12 W
<b>Rated Input Voltage Frequency</b>	100-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Cable Primary</b>	Yes
<b>Primary Connection</b>	Power plug
<b>Primary Cable Length</b>	1.6 m
<b>Dimmable</b>	Yes
<b>Control technology</b>	Touch-Sensor
<b>Motion Detector</b>	No

<b>Light Source</b>	LED, Light source not changeable
<b>Lightcolor</b>	Warm white (WW)
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	950 lm
<b>Luminous Efficiency</b>	79.2 lm/W
<b>Rated Angle of Reflection</b>	120 Degree
<b>Distribution Characteristic 120°</b>	DLS

<b>Swivel Angle</b>	135 Degree
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Length</b>	355 mm
<b>Diameter</b>	150 mm
<b>Base height</b>	16 mm
<b>Base diameter</b>	160 mm

<b>Product weight</b>	1460 g
<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-20 to 50 °C
<b>IP Protection Class</b>	IP 20
<b>Life Time L70 / B50</b>	25000 h
<b>Switching Cycles</b>	12500
<b>Power Consumption</b>	10 kWh/1000h
<b>Energy Efficiency Class</b>	G