



The lights of the SLIM series includes 1-lamp, 3-lamp pendant lights and matching pendant lights for the DEKO-LIGHT track system. The luminaire body made of die-cast aluminum is always the same size (300 x 39mm). This means that several SLIM models can be combined in larger rooms. The pendant luminaires for ceiling installation with a maximum suspension of 180 cm are available as single and three-lamp versions, the three-lamp version with both elongated or round base, depending on the arrangement of the lights.

Special features

- Aluminum Die Casting
- Textile cable
- Particularly glare-free, thanks to low UGR - value
- Suspension up to 1800 mm

Housing Material	Aluminium	Base height	26 mm
Housing Color	Black	Pendulum Length max.	1800 mm
Material of Lens	PMMA	Working Temperature	-20 to 45 °C
Colour of Lens	Transparent	Storage Temperature	-20 to 65 °C
Surface Structure of Lens	Structured	IP Protection Class	IP 20
Protection Class	Protection class I/protective grounding	Life Time L70 / B50	50000 h
Rated Input	15 W	Switching Cycles	100000
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Power Consumption	15 kWh/1000h
Power Supply Unit incl.	Yes	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Connection Type	Clamp		
Dimmable	Yes		
Control technology	Leading-edge dimmer, Trailing-edge dimmer		
Motion Detector	No		
Light Source	LED, Light source changeable TC		
Color Temperature	2700 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	1500 lm		
Rated Angle of Reflection	24 Degree		
UGR	19		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	3		
Light characteristics	Direct		
Light direction	Below		
Height	300 mm		
Diameter	39 mm		
Base length	370 mm		
Base width	80 mm		