

**Special features**

- Including 2 m connecting cable with IP44 plug
- Including wireless remote control with approx. 20 m range.

<b>Housing Material</b>	Plastic	<b>IP Protection Class Plug</b>	IP 44
<b>Housing Color</b>	Black	<b>Life Time L70 / B50</b>	25000 h
<b>Protection Class</b>	Protection class I/protective grounding	<b>Switching Cycles</b>	100000
<b>Rated Input</b>	32 W	<b>Power Consumption</b>	32 kWh/1000h
<b>Rated Input Voltage</b>	100-240 V/AC 50 / 60 Hz		
<b>Frequency</b>			
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Cable Primary</b>	Yes		
<b>Primary Connection</b>	Power plug IP44		
<b>Primary Cable Length</b>	2 m		
<b>Connection Type According to Standard</b>	Typ Y		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	RF 2,4 GHz		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Colour Consistency</b>	6 SDCM		
<b>Rated Luminous Flux</b>	1060 lm		
<b>Rated Angle of Reflection</b>	150 Degree		
<b>Light Distribution</b>	Symmetric		
<b>Distribution Characteristic 120°</b>	DLS		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Top		
<b>Length</b>	178 mm		
<b>Width</b>	81 mm		
<b>Height</b>	215 mm		
<b>Working Temperature</b>	-20 to 50 °C		
<b>Storage Temperature</b>	-40 to 60 °C		
<b>IP Protection Class Lamp</b>	IP 65		