



Little helper, big effect. With the HERCULIS display lights in a high-quality aluminium housing, you can reach all corners of a display case. To do so, the lamp head with its 40° light emission angle can be freely rotated and swivelled in any direction. In addition, the intelligent cable routing and the ready-to-use system enable easy surface and recessed mounting in display cases, counters, sales areas or in living rooms.

#### Special features

- High output with compact design
- Rotatable and swivelling heads
- For panel and surface mounting
- Intelligent cable routing
- Ready-to-use system

**Housing Material** Die-cast aluminium  
**Housing Color** Black

**Protection Class** Protection class III/safety extra-low voltage

**Operating Mode** Constant current

**Rated Input** 1 W

**Rated Input Voltage** 3 V/DC

**Rated Current** 350 mA

**Power Supply Unit incl.** No

**Connection Cable Secondary** Yes

**Secondary Connection** Plug mini AMP

**Secondary Cable Length** 1 m

**Dimmable** No

**Motion Detector** No

**Light Source** LED, Light source not changeable

**Color Temperature** 3000 K

**Colour Consistency** 6 SDCM

**Colour Rendering Index (Ra)** 90

**Rated Luminous Flux** 100 lm

**Rated Angle of Reflection** 40 Degree

**Distribution Characteristic 120°** DLS

**Swivel Angle** 180 Degree

**Light Exit Surfaces** 1

**Light characteristics** Direct

**Light direction** Top

**Height** 42.2 mm

**Diameter** 31 mm

**Base height** 5 mm

**Base diameter** 31 mm

**Working Temperature** -10 to 45 °C

**Storage Temperature** -10 to 45 °C

**IP Protection Class** IP 20

**Life Time L70 / B50** 30000 h

**Switching Cycles** 50000

**Power Consumption** 1 kWh/1000h

**Energy Efficiency Class** G