



The LED pendant lamp has transparent glass for direct and indirect light distribution that is almost see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare.

This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light not only stands out in any type of office environment.

Special features

- Very low glare value
- Light colour adjustable in 2 stages
- Transparent luminous element
- Max. suspended mounting 1,800 mm

Housing Material	Aluminium
Housing Color	Aluminum
Material of Lens	PMMA
Protection Class	Protection class I/protective grounding
Rated Input	53 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000/4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	6100 lm
Rated Angle of Reflection	360 Degree
UGR	19
Light Distribution	Symmetric
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	2
Light characteristics	Direct
Light direction	Top, Below

Length	295 mm
Width	1195 mm
Height	12 mm
Base length	570 mm
Base width	80 mm
Base height	50 mm
Pendulum Length max.	1800 mm

Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 40 °C
IP Protection Class	IP 40

Life Time L70 / B50	50000 h
Life Time L80 / B50	50000 h
Switching Cycles	25000
Power Consumption	53 kWh/1000h
Energy Efficiency Class	E