



#### Produkteigenschaften

Einbautiefe	70 mm
Außendurchmesser	75 mm
Auslassöffnung	73 mm
Leuchteneinbauhöhe	67 mm
Klappenlänge	50 mm
Klappenbreite	26 mm
Rand Lampenöffnung	5 mm
Stärke Kappe	0,8 - 1,0 mm
Lampenleistung max.	35 W
Farbe	transparent

#### Schutzkappe Niedervolt / LED 75 mm - Für aktiven Schutz in Hohldecken

- » Keine Brandgefahr
- » Intakte Dampfsperre
- » Lebensdauer der Leuchtmittel gewährt
- » Optimal geeignet für Halogeneinbaustrahler, LED
- » Einfacher, nachträglicher Einbau
- » Schützt LED vor Überhitzung
- » Aktiver Brandschutz
- » Nicht geeignet für Kaltlichtlampen

Serie	-
Artikelnummer	P009-D
Kategorie	Brandschutz
Montageart	-
Einsatz	Deckenbeleuchtung
EAN	4260182060155

#### Materialeigenschaften

Material	Silikon-Kautschuk
----------	-------------------



**Protective cap low voltage / LED 75 mm -  
For active protection in hallow ceilings**

- » Intact vapor barrier
- » Lifetime of the illuminants guaranteed
- » Ideally suited for recessed halogen spotlights, LED
- » Easy retrofit installation
- » Protects LED from overheating
- » Active fire protection
- » Not suitable for cold light lamps

**Product features**

Installation depth	70 mm
Outer diameter	75 mm
Outlet opening	73 mm
Luminaire installation height	67 mm
Flap length	50 mm
Flap width	26 mm
Edge lamp opening	5 mm
Thickness cap	0,8 - 1,0 mm
Lamp power max.	35 W
Color	transparent

Series	-
Article No.	P009-D
Category	Fire protection
Type of installation	-
Use	ceiling lighting
EAN	4260182060155

**Material properties**

Material	Silicone-rubber
----------	-----------------