





Note: position of the inspection hole is on the crimp collar for 2.5mm² female contacts

base material: copper alloy
coating: GoldTec

Part no. 09 15 000		Ø	Wire gauge		Stripping length	Recommended crimping tools			
male contact	female contact		mm ²	AWG		09 99 000 0888	09 99 000 0001	09 99 000 0110	09 99 000 0021
6307	6407	0,90	0,14-0,37	26-22	8	X	X		
6304	6404							X	X
6303	6403	1,15	0,5	20		X	X	X	X
6305	6405	1,30	0,75	18		X	X	X	X
6302	6402	1,45	1	18		X	X	X	X
6301	6401	1,75	1,5	16		X	X	X	X
6306	6406	2,25	2,5	14		6	X	X	



 All Dimensions in mm Original Size DIN A4		Scale 2:1	Free size tol.		Ref.
 All rights reserved Department EL PD		Created by SPRENB	Inspected by RIEPE	Standardisation 302077	Date 2021-01-13
HARTING D-32339 Espelkamp		Title Han D-SMC FC/MC-CRT-GT			State Final Release
		Type TB	Number 09 15 000 6YYY		Doc-Key / ECM-Nr. 100133088/UGD/004/C 500000187121
					Rev. C Page 1/1