



Whether in high-bay warehouses, in large sales areas or in extensive presentation spaces - ALUDRA series pendant lamps prove highly capable as universal high-bay downlighters for use at height. Thanks to their high luminous flux, wide light emission angle and IK10 impact strength class, ALUDRA lights bring functional light to large areas safely and reliably.

Special features

- Including 3 m connecting cable
- High impact resistance
- High luminous intensity

Housing Material	Aluminium
Housing Color	Black
Protection Class	Protection class I/protective grounding
Rated Input	160 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	With free strand / conductor ends
Primary Cable Length	3 m
Dimmable	No
Motion Detector	No

Switching Cycles	25000
Power Consumption	160 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	5000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	24450 lm
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	165 mm
Diameter	360 mm

Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 65
IK Protection Class	IK10

Life Time L70 / B50	50000 h
----------------------------	---------

