



Multifaceted eye-catcher - With its triangular-shaped openings, the angular matt white shade of the Asterope standing lamp produces a multifaceted light pattern that extravagantly and yet harmoniously compliments almost any ambience. A single E27 lamp with max. 100 watts serves as the light source.

#### Special features

- Metal housing
- Exchangeable lamp (E27)
- Including connecting cable with switch

|                                      |   |
|--------------------------------------|---|
| <b>Housing Material</b>              | Metal                                     |
| <b>Housing Color</b>                 | White                                     |
| <b>Housing Surface</b>               | Matt                                      |
| <b>Protection Class</b>              | Protection class II/protective insulation |
| <b>max. Power</b>                    | 1x max. 40 W                              |
| <b>Rated Input Voltage Frequency</b> | 220-240 V/AC 50 / 60 Hz                   |
| <b>Socket Description</b>            | E27                                       |
| <b>Socket Quantity</b>               | 1   |
| <b>Connection Cable Primary</b>      | Yes                                       |
| <b>Primary Connection</b>            | Power plug                                |
| <b>Primary Cable Length</b>          | 2.3 m                                     |
| <b>Motion Detector</b>               | No  |
| <b>Execution</b>                     | Without lamp                              |
| <b>Light Exit Surfaces</b>           | 1   |
| <b>Light characteristics</b>         | Direct                                    |
| <b>Light direction</b>               | Top, Below, Side, Rear, Front             |
| <b>Height</b>                        | 1600 mm                                   |
| <b>Diameter</b>                      | 210 mm                                    |
| <b>Base height</b>                   | 30 mm                                     |
| <b>Base diameter</b>                 | 250 mm                                    |
| <b>Product weight</b>                | 6000 g                                    |
| <b>Working Temperature</b>           | -5 to 40 °C                               |
| <b>Storage Temperature</b>           | -10 to 60 °C                              |
| <b>IP Protection Class</b>           | IP 20                                     |