



SCULPTORIS series pendant lamps boast an impressive matte visual design and luminous ring. With high luminous intensity and large light emission angle, the series offers flexible applications in many different areas, whether in living areas or for providing imposing lighting solutions to office spaces.

Special features

- Light colour adjustable in 2 stages
- Uniform illumination
- Circumferential diffuser
- Suspended mounting up to 1,800 mm

Housing Material	Aluminium
Housing Color	White
Housing Surface	Matt
Material of Lens	Plastic
Surface Structure of Lens	Opal
Protection Class	Protection class I/protective grounding
Rated Input	27 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No
Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1700 lm
Rated Angle of Reflection	150 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	NDLS
Light Exit Surfaces	1
Light characteristics	Direct, Indirect
Light direction	Top, Below
Height	130 mm
Diameter	450 mm
Base height	65 mm
Base diameter	230 mm
Pendulum Length max.	1000 mm

Working Temperature	-10 to 45 °C
Storage Temperature	-10 to 45 °C
IP Protection Class	IP 20
Life Time L70 / B50	20000 h
Switching Cycles	15000
Power Consumption	27 kWh/1000h
Energy Efficiency Class	E