

Han-Mod RJ45 IDC cable jack 8P AWG 24-22



Part number	09 14 545 1562
Specification	Han-Mod RJ45 IDC cable jack 8P AWG 24-22
HARTING eCatalogue	https://b2b.harting.com/09145451562

Image is for illustration purposes only. Please refer to product description.

Identification

Element Data connectors Specification Han [®] RJ45 cable jack
Specification Han [®] RJ45 cable jack
Version
Termination method IDC termination
Gender Female
Number of contacts 8

Technical characteristics

Conductor cross-section	AWG 24 AWG 22
Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s
Limiting temperature	-40 +70 °C
Mating cycles	≥500
Material properties	
Material (insert)	Polyamide (PA)

Material (insert)	Polyamide (PA)
Material (shielding)	Zinc die-cast, nickel-plated
Material flammability class acc. to UL 94	V-0

Page 1 / 2 | Creation date 2022-09-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
Approvals	DNV GL

Commercial data

Packaging size	1
Net weight	28 g
Country of origin	Latvia
European customs tariff number	85389099
GTIN	5713140021587
eCl@ss	27440218 Module for industrial connectors (data)