

**Product Features**

"splice box, extensible, 19"/1U, 24xST, OM3, metal"

- sheet steel housing, powder coated
- labelled ports
- with slide-in unit, max. pullout depth ca. 20 cm
- can be tilted downwards when opened
- can be locked with knurled screws
- the box can be offset by 40 mm towards the rear
- 2 splice cassettes for holding 12 or 24 pigtails
- can be equipped with max. 4 splice cassettes (fixed)
- inserted crimp splice holder
- ready to splice with exposed and inserted pigtails incl. 24 x ST - ceramic couplings
- SC-fibre pigtails G50/125 Åm, 2 m, MM PC, grade B
- with test protocol for all fibres incl. serial number
- 4 x PG16 - cable glands in the back (each 2 x right/left)
- 1 x PG16 - cable gland in scope of delivery
- light grey (similar RAL 7035)

**Features**

General	
Surface	steel sheet, powder-coated
Classification	OM3
Protection class IP	20
Halogen Free	Yes
Country of manufacture	DE
GTIN (EAN)	4043921664612
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Dimensions/Weights without packaging	
Length mm	482
Width mm	231
Height mm	44
Net weight piece kg	2,74
Certifications	
RoHS conform	Yes

**Spleissbox 24xST OM3**

Article no.: 228031024

Color: lightgrey (ähnlich RAL-Nr. 7035)

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	2,931
Packaging unit Width mm	500
Packaging unit Height mm	50
Packaging unit Depth mm	325
References	
Accessories	228041002, 228041102, 228041202, 228061000, 228061200, 228070000, 228070100, 228070200, 228070312
Similar article	228030024, 228030524, 228031006, 228031012, 228031124, 228031224