



Special features

- Adjustable colour temperature
- High colour reproduction value
- Swivel-mounted

Housing Material	Aluminium
Housing Color	Silver
Housing Surface	Brushed
Material of Lens	Glass
Colour of Lens	White
Surface Structure of Lens	Satined

Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	8 W
Rated Input Voltage	24 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	0.24 m
Dimmable	Yes
Control technology	Dimmable via optional controller
Motion Detector	No

Light Source	LED, Light source not changeable
Colour Temperature	2500-6500 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	700 lm
Luminous Efficiency	87.5 lm/W
Rated Angle of Reflection	45 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	25 Degree
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	46 mm
Diameter	78 mm
Installation Depth	50 mm
Cut Out Diameter	68 mm
Product weight	116 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20

Life Time L70 / B50	50000 h
Switching Cycles	100000
Power Consumption	8 kWh/1000h
Energy Efficiency Class	G

