

Basic-A1

Surface mounted luminaire - Direct light distribution

Article code: BA1ABE-840E-D600



Illustrations may only be similar and serve as an orientation.




Basic-A1. LED. Surface mounted luminaire for wall or ceiling mounting with minimalist edge. Luminaire body made of high-quality aluminum profile. Surface finish Jet Black. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. UGR<=19. Switchable. DxH (round). D=600mm. H=75mm. Low-power current. 3860lm.

25W. 8,9kg. Binning initial <= MacAdam 3. IP40. Protection class I. CE, UKCA marking. Prüfzeichen: ENEC. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 and 50001:2018 certified.

Basic-A1

Surface mounted luminaire - Direct light distribution

Article code: BA1ABE-840E-D600



Customer / Project: _____

Note: _____

Productname	Basic-A1
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Jet Black
Light characteristics	Direct light distribution
Colour temperature	4000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Microprismatic screen
Control	Switchable
Length L/Diameter D (mm)	D=600mm
Height H (mm)	H=75mm
Current/Power	Low-Power
Luminous Flux	3860lm
Power consumption	25W
Degree of protection	IP40
Certification	Prüfzeichen: ENEC
LED lifetime	L90B10 (tq 25°C) = 50.000h
UGR	UGR<=19
Photometric code	8 40 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	8,9kg

