


INSTRUCTION

pirola



REGIOLUX

Regiolux GmbH
Hellinger Str. 3
D-97486 Königsberg/Bay.
T 09525 89-0
http://www.regiolux.de
info@regiolux.de

PGPC 5011
PGPC-DV 5012

-DV
1x 2x

OFF

Achtung:
Leuchte nicht öffnen!
Garantieverlust!

Attention:
Don't open the luminaire!
Loss of Guarantee!

Attention:
N'est pas ouvrir le luminaire!
Perte de garantie!

Atención:
Non abrir la luminara!
Pérdida de garantía!

	L	A1	A3	A4	A
PGPC/1200	1200	700	500+A	900	min. 75
PGPC/1500	1500	900	600+A	1200	min. 75

max. 6 A

35±2
8±1
=1,5 mm² Ø min. 6mm
Ø max. 10mm

-DV	DALI	ET
L = L	L = L	L (Konverter) = L...
N = N	N = N	N = N
PE = PE	PE = PE	PE = PE
+ = DALI	+ = DALI	= L...
- = DALI	- = DALI	= L...

DIN96 ø6

20 cm

1

2

Klick!

-DV

1

2 fix!

no use

! IP65

Klick!

SDT Basic

SDLA 1890 0058 100

Klick!

DKF-HBK 5976 1100 100

DKF 5976 1360 100
5976 1580 100