



Product features and key data

| | |
|---|--|
| Luminaire type | Exclusive free-standing LED luminaire with 2 separately controllable luminaire heads, direct and indirect distribution. |
| Mounting method | Positioning |
| Luminaire optic | With its wide, slightly asymmetric light distribution, the direct component of the luminaire provides very uniform illumination of the desk surface. The indirect component with Lambertian light distribution provides optimum room illumination. |
| Connected load | 220 W |
| Colour temperature | 3.000 K |
| Rated luminous flux | 30.600 lm |
| Luminous efficacy | 139 lm/W |
| Interchangeability lightsource | Yes - interchangeable |
| Service life | L80 (25 °C) = 50.000 h |
| Colour rendering index | 80 |
| Colour tolerance | 3 SDCM |
| Photobiological class | Group 0 - no risk |
| Luminaire colour | RAL9005 Jet black |
| Luminaire body | Luminaire body made of extruded aluminium profile and die-cast aluminium. Luminaire base H-shaped. |
| Electrical version | With electronic control gear unit, dimmable (integrated). |
| Connection method | Mains plug |
| Dimming range | 1 - 100 % |
| Mains frequency | 50/60 Hz |
| Mains voltage | 220 - 240 V |
| Total harmonic distortion < % | 14 % |
| Ingress Protection (IP) rating | IP20 |
| Protection rating on room side | IP20 |
| Protection class | I |
| Impact resistance (IK) | IK02 |
| Hot wire resistance | 650 °C |
| Ambient temperature | 25 °C |
| Max. Luminaires B10 | 7 |
| Max. Luminaires B16 | 12 |
| Max. Luminaires C10 | 12 |
| Max. Luminaires C16 | 20 |
| Net length | 1.334 mm |
| Net width | 450 mm |
| Net height | 2.000 mm |
| Weight | 25,2 kg |

light distribution curve



LuceoS S-T SMC PAW-IL 300-830 ETDI 05 (LEO1)
TX369400 ■ C0 - C180
■ C90 - C270
 DIN 5040: E03
 UTE: 0,08 D + 0,91 T
 CEN Flux Code: 53 86 96 8 100 49 82 98 92



LuceoS S-T SMC PAW-IL 300-830 ETDI 05 (LEO2)
TX369909 ■ C0 - C180
■ C90 - C270
 DIN 5040: E03
 UTE: 0,08 D + 0,91 T
 CEN Flux Code: 53 86 96 8 100 49 82 98 92

Offer text

Exclusive free-standing LED luminaire with 2 separately controllable luminaire heads, direct and indirect distribution. For standard-compliant illumination of twin and four-person workstations. In terms of design and photometric properties, the free-standing luminaire harmonises with suspended and surface-mounted luminaires as well as other free-standing luminaire versions in the project. The luminaire is delivered in 4 packages to protect the individual components. Pre-assembled luminaire head for quick and easy installation in just three steps. With its wide, slightly asymmetric light distribution, the direct component of the luminaire provides very uniform illumination of the desk surface. The indirect component with Lambertian light distribution provides optimum room illumination. Glare evaluation according to UGR rating (EN 12464-1) < 16. VDU workstation-compliant in accordance with 12464-1 Luminaire luminous flux 30600 lm, connected load 220,00 W, luminous efficiency of luminaire 139 lm/W. Light colour warm white, correlated colour temperature (CCT) 3000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) ≤ 3 SDCM, Mean rated service life $L80(t_a 25^\circ C) = 50,000$ h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Luminaire body made of extruded aluminium profile and die-cast aluminium. Luminaire base H-shaped. Surface powder-coated satin matt, colour black (RAL 9005). Further colours available on request. Luminaire height: 2000 mm, Length / width of base: 800 mm / 450 mm, Length / width of luminaire head: 1334 mm x 290 mm, High luminaire head: 23 mm. Supporting column dimensions: 80 mm x 30 mm. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP20, impact resistance level in accordance with IEC 62262: IK02, testing temperature of wire glow test in accordance with IEC 60695-2-11: 650 °C. Weight: 25,2 kg. Connection via flexible connection cable 3 x 1 mm² (safety plug and C14 cold-device socket), length approx. 3000 mm. Alternative connector types available: Connection plug type J SEV, Switzerland. Connection plug type BS, British Standard 1363. With connection cable. With electronic control gear unit, dimmable (integrated). The control gear unit is replaceable in accordance with the ecodesign requirements (VO (EU) 2019/2020). For each luminaire head, the operating elements (2-way push-buttons) are integrated in the supporting column. These enable separate switching and dimming of the direct and indirect components of the individual luminaire head. With Smart Connect equipment for combination with a LiveLink Lightgrid Controller. The luminaire features an integrated daylight- and HF presence sensor with motion direction detection. Smart Connect versions of desktop luminaires in a room can be connected via Bluetooth to form an interactive group of luminaires. The initial detection of movement by any luminaire within the group causes all group devices to switch on at basic lighting level (approx. 300 lx, indirect component). Subsequent detection in the close range of a luminaire triggers this into workplace mode by switching on of the direct component. Parameterisation of the Smart Connect functions is password-protected using a smartphone and an app. Operating the lighting functions is implemented manually via 3 operating elements and via Smartphone app. Communication between the connected luminaires and the smartphone is via Bluetooth Low Energy v 5.0. Single luminaires as well as luminaire groups can be controlled with up to 4 battery-free and wireless radio buttons, which are available as separately ordered accessories. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.