



This pendant lamp is distinct for its transparent luminous element. The surface is almost completely see-through when switched off. When the light is switched on, the pane distributes the light almost entirely without glare. This pendant lamp is fully office-compatible with a glare value [UGR] of under 19. Bright, efficient and with a sophisticated design, this light stands out in any type of office environment.

Special features

- Very low glare value
- Transparent luminous element
- Max. suspended mounting 1,500 mm

Housing Material	Aluminium
Housing Color	White
Material of Lens	Acryl
Protection Class	Protection class I/protective grounding
Rated Input	53.3 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Storage Temperature	-10 to 40 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Switching Cycles	12500
Power Consumption	54 kWh/1000h
Energy Efficiency Class	E

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	6612 lm
Rated Angle of Reflection	150 Degree
UGR	19
Light Distribution	Symmetric
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	2
Light characteristics	Direct
Light direction	Top, Below

Height	12.5 mm
Diameter	580 mm
Base height	45 mm
Base diameter	250 mm
Pendulum Length max.	1500 mm

Working Temperature	-5 to 40 °C
----------------------------	-------------