

**Special features**

- Including connecting cable

Housing Material	Stainless steel	Product weight	5000 g
Housing Color	Silver	Working Temperature	-20 to 40 °C
Material of Lens	Glass	Storage Temperature	-10 to 60 °C
Protection Class	Protection class III/safety extra-low voltage	IP Protection Class	IP 67
Operating Mode	Constant voltage	IK Protection Class	IK07
Rated Input	42.8 W	Load Force max.	20 kN
Rated Input Voltage	24 V/DC	Life Time L70 / B50	35000 h
Power Supply Unit incl.	No	Switching Cycles	20000
Connection Cable Secondary	Yes	Power Consumption	43 kWh/1000h
Secondary Connection	WEIPU plug 4-pole		
Secondary Cable Length	0.5 m		
Dimmable	Yes		
Control technology	Dimmable via optional controller		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Colour Consistency	6 SDCM		
Rated Luminous Flux	700 lm		
Luminous Efficiency	16.4 lm/W		
Rated Angle of Reflection	30 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		
Length	1025 mm		
Width	68 mm		
Height	31.5 mm		
Installation Depth	80 mm		
Cut Out Length	1004 mm		
Cut Out Width	58 mm		