



Our light chameleon: Sophisticated design meets innovative dimming technology. The further you dim the CANOPUS, the warmer the light becomes. No light comes close to real candlelight - but the CANOPUS is not far off. Elegant, glare-free and modern ambient lighting at its best!

#### Special features

- Very high colour reproduction value
- Dim to warm
- Glare-free light

<b>Housing Material</b>	Die-cast aluminium	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Color</b>	Silver	<b>Switching Cycles</b>	100000
<b>Protection Class</b>	Protection class I/protective grounding	<b>Power Consumption</b>	16 kWh/1000h
<b>Rated Input</b>	16 W	<b>Energy Efficiency Class</b>	G
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	No		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source not changeable		
<b>Colour Temperature</b>	2000-3000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	90		
<b>Rated Luminous Flux</b>	900 lm		
<b>Rated Angle of Reflection</b>	138 Degree		
<b>Distribution Characteristic 120°</b>	NDLS		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below, Rear		
<b>Length</b>	140 mm		
<b>Width</b>	115 mm		
<b>Height</b>	265 mm		
<b>Base length</b>	110 mm		
<b>Base width</b>	110 mm		
<b>Base height</b>	33 mm		
<b>Working Temperature</b>	-5 to 40 °C		
<b>Storage Temperature</b>	-10 to 60 °C		
<b>IP Protection Class</b>	IP 20		