



Product Features

Basic-line splice box, extensible, 19"/1U, 6xLC-D, OM3, aqua

- sheet steel housing, powder coated
- labelled ports
- with slide-in unit
- can be tilted downwards when opened
- front quick release (push-pull)
- splice cassette for holding 12 or 24 pigtails
- inserted crimp splice holder
- prepared with pigtails inserted in bundle of 12 incl. 6 x LC-D ceramic couplings
- 12 LC-fibre pigtails G50/125 µm, 2 m, MM PC, grade C
- with test protocol for all fibres incl. serial number
- mounted blind stops by less than 12 ports
- 2 x PG13,5/M20 - cable glands in the back (each 2 x right/left)
- 1 x PG13.5 gland in scope of delivery
- black (similar to RAL 9005)

Features

General

| | |
|--------------------------|----------------------------|
| Surface | steel sheet, powder-coated |
| Classification | OM3 |
| Protection class IP | 20 |
| Statistical goods number | 85367000 |
| Country of manufacture | DE |
| GTIN (EAN) | 4043921666913 |

Mounting types

| | |
|-------------------------------------|-----|
| (19-inch)-installation, 1 rack unit | Yes |
|-------------------------------------|-----|

Dimensions/Weights without packaging

| | |
|---------------------|-------|
| Length mm | 482 |
| Width mm | 245 |
| Height mm | 44 |
| Net weight piece kg | 1,211 |

Certifications

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|

BL-Spleissbox 6xLC-D OM3 aqua

Article no.: 2280300060

Color: black (ähnlich RAL-Nr. 9005)

| Logistics Information | |
|--------------------------|--|
| Packaging | box |
| Packaging unit Quantity | 1 |
| Packaging unit Weight kg | 1,356 |
| Packaging unit Width mm | 305 |
| Packaging unit Height mm | 60 |
| Packaging unit Depth mm | 510 |
| References | |
| Accessories | 228040002, 228040102, 228040302, 228060000, 228060100, 228060300, 228070000, 228070100, 228070200, 228070312 |