Surface-mounted ceiling light Helen II, 20 W, 3000/4000/5500 K, Silver










The 3-in-1 ceiling light - with the Helen, you get three lights in one. The LEDs can be switched from warm white to neutral white or cold white using a small switch on the printed circuit board. Thanks to IP54, the ceiling light is suitable for all areas of the home, such as the kitchen, bathroom, living areas and even outdoors. The same light in both the garage and kitchen? No problem with the Helen. Whilst you would probably prefer cold white in the garage, warm white is the top pick for living areas and usually neutral white in the kitchen and bathroom. All bases are covered with just one light.



Special features

- Light colour adjustable in 3 stages
- Splash water protected

Housing MaterialPlasticHousing ColorSilverHousing SurfaceBrushed

Material of Lens Polycarbonate - PC

Colour of Lens White
Surface Structure of Lens Satined

Protection Class Protection class II/protective

insulation

Rated Input 20 W

Rated Input Voltage Frequency $\,$ 220-240 V/AC 50 / 60 Hz

Power Supply Unit incl.YesConnection TypeClampDimmableNoMotion DetectorNo

Light Source LED, Light source not changeable

Color Temperature 3000/4000/5500 K

Colour Consistency6 SDCMColour Rendering Index (Ra)80Rated Luminous Flux1800 lmRated Angle of Reflection115 DegreeDistribution Characteristic 120°NDLS

Light Exit Surfaces1Light characteristicsDirectLight directionBelow

 Height
 89 mm

 Diameter
 351 mm

 Base height
 20 mm

 Base diameter
 326 mm

Working Temperature -20 to 40 °C Storage Temperature -20 to 50 °C IP Protection Class IP 54

 Life Time L70 / B50
 30000 h

 Switching Cycles
 15000

 Power Consumption
 20 kWh/1000h

Energy Efficiency Class G

