



The pendant lamps of the new MEROPE series combine timeless elegance and subdued modernity. Available in the diameters 400, 600 and 800 mm, the light colour [3,000/4,000 K] can be selected before installation using a CCT switch. The outside is finished in brushed aluminium in the colours white, silver, coffee and black.

#### Special features

- High luminous flux
- Light colour adjustable in 2 stages
- Suspended mounting up to 1,800 mm

<b>Housing Material</b>	Aluminium	<b>Working Temperature</b>	-10 to 45 °C
<b>Housing Color</b>	White	<b>Storage Temperature</b>	-10 to 45 °C
<b>Housing Surface</b>	Matt	<b>IP Protection Class</b>	IP 20
<b>Material of Lens</b>	Acryl	<b>Life Time L70 / B50</b>	30000 h
<b>Surface Structure of Lens</b>	Satined	<b>Switching Cycles</b>	20000
<b>Protection Class</b>	Protection class I/protective grounding	<b>Power Consumption</b>	42 kWh/1000h
<b>Rated Input</b>	42 W	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class E.
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	3100/3200 lm		
<b>Rated Luminous Flux 2</b>	3200 lm		
<b>Light Distribution</b>	Symmetric		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below		
<b>Height</b>	60 mm		
<b>Diameter</b>	580 mm		
<b>Base height</b>	65 mm		
<b>Base diameter</b>	220 mm		
<b>Pendulum Length max.</b>	1800 mm		