


Artikel-Nr. 17528000



White light radio controller for controlling the one-color LED modules in the white light range or for controlling dim2warm flexible printed circuit boards 15312003 / 15362003. Controller: voltage: 12-24 V DC, current: maximum 10 A (2 x 5 A or 3 x 3.33 A), power: maximum 120 W / 240 W (12 V DC / 24 V DC), control: negative (common anode), control signal: PWM, radio frequency: 869.5 MHz, range (visual contact): up to 20 m, ambient temperature (ta): 0 °C to +40 °C. Controller connection using screw terminals, (Dimensions: L 178 x W 46 x H 18 mm. Material: Plastic, delivery: including strain relief. Controller per remote control: maximum 4 (for optimum radio connection) Remote control: Voltage (battery): 4.5 V DC - 3 x AAA (not included in the scope of delivery), Radio frequency: 869.5 MHz, transmission power (Ps) < 0 dBm, Range (visual contact): up to 20 m, Ambient temperature (ta): 0 °C to +40 °C, Dimensions: L 120 x W 48 x H 18 mm. Material: Plastic. Function scope:- On / Off. Dimming using a touch wheel - Save keys S1 / S2- Selection keys 25% / 50% / 75% / 100% brightness. Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V 24V, Power: 240W.

Artikel-Nr.	17528000
Stand:	06.12.2021 16:06

Description	Weißlicht-Set (Controller inkl. Fernbedienung)	Voltage	12V 24V
Material	Plastic	Enviroment temprature (ta)	0 °C bis +40 °C
Degree of protection	IP20	Circuit type	Parallel conduction
Protection class	III	Transmission frequency	869.5 MHz