



The pendant lamp is an appropriate addition to the OFFICE THREE MOTION standing lamp. As the glare value is under 10, this sophisticated light can be thought of as being almost entirely glare-free. The LEDs directed upwards create room lighting, whilst the LEDs directed downwards emit clearly defined and powerful light onto the work area.

Special features

- Very low UGR value
- High luminous flux
- Controlled using DALI 2.0
- Max. suspended mounting 2,500 mm

Housing Material	Aluminium	Pendulum Length max.	2500 mm
Housing Color	Silver	Working Temperature	-5 to 40 °C
Material of Lens	Plastic	Storage Temperature	-10 to 50 °C
Protection Class	Protection class I/protective grounding	IP Protection Class	IP 20
Rated Input	60 W	Life Time L70 / B50	50000 h
Rated Input Voltage Frequency	200-240 V/AC 50 / 60 Hz	Life Time L80 / B10	50000 h
Power Supply Unit incl.	Yes	Switching Cycles	25000
Connection Type	Clamp	Power Consumption	60 kWh/1000h
Dimmable	Yes	Energy Efficiency Class	E
Control technology	DALI 2 / DT6		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	7000 lm		
Rated Angle of Reflection	115 Degree		
Rated Angle of Reflection 2	55 Degree		
UGR	6		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		
Length	1179 mm		
Width	64 mm		
Height	35 mm		
Base length	600 mm		
Base width	56.5 mm		
Base height	35 mm		