



<b>Housing Material</b>	Die-cast aluminium	<b>Life Time L70 / B50</b>	50000 h
<b>Housing Color</b>	Grey	<b>Switching Cycles</b>	50000
<b>Material of Lens</b>	Glass	<b>Power Consumption</b>	8 kWh/1000h
<b>Protection Class</b>	Protection class I/protective grounding	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class D.
<b>Operating Mode</b>	Constant current		
<b>Rated Input</b>	7.4 W		
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Cable Gland Diameter</b>	12 mm		
<b>Dimmable</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Consistency</b>	3 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	237/256 lm		
<b>Rated Luminous Flux 2</b>	256 lm		
<b>Rated Angle of Reflection</b>	50 Degree		
<b>Rated Angle of Reflection 2</b>	100 Degree		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Length</b>	120 mm		
<b>Width</b>	100 mm		
<b>Height</b>	600 mm		
<b>Working Temperature</b>	-20 to 40 °C		
<b>Storage Temperature</b>	-20 to 50 °C		
<b>IP Protection Class</b>	IP 65		
<b>IK Protection Class</b>	IK06		